



# THREE-LAYER GLUED WOOD PANEL

*Premium solid wood for design and functionality*

Our three-layer glued wood panel is a dimensionally stable and easy-to-work solid wood material that combines high quality with clean aesthetics.

The panels are a perfect choice for those seeking an exclusive material for doors in kitchens, bathrooms, and wardrobes, or as furniture components for tabletops and shelves.

The front side is color-sorted to provide a uniform and elegant appearance – ready to elevate your design to the next level!

The three-layer panels are delivered in 19 mm thickness (5+9+5) in standard formats in Oak, Birch, and Ash.



- Dimensionally stable construction – minimizes movement and cracking
- Easy to work with – saves time in production
- Color-sorted front – provides an exclusive and uniform appearance
- Fast deliveries – thanks to our stock availability
- Made from Oak, Birch, and Ash – for different expressions and needs





## ORDER SPECIFICATION– THREE LAYER WOOD PANEL

Please fill out the form and send it to [order@kglist.se](mailto:order@kglist.se).  
 A correctly completed order ensures that we can process your request as quickly as possible.  
 We will follow up with an order confirmation to the email address provided.

Thickness (mm)	Width (mm)	Length (mm)	Oak	Birch	Ash
19	604	400			
19	804	400		Not available	Not available
19	604	775		Not available	Not available
19	804	775		Not available	Not available
19	404	900		Not available	
19	604	900			
19	904	900			
19	604	1410			
19	604	2184			
19	604	2410			

Company name		Contact person	
VAT. nr		Email order confirmation	
Billing adress		Delivery adress (if different)	
Phone nr		Preferred delivery week	
Email for PDF invoice		Other instructions	

**Receiving Goods** It is important that staff are present during daytime hours to receive the delivery and that correct delivery details are provided in the order.

If the carrier is unable to unload the goods due to lack of contact for reception or incorrect information, a missed delivery fee will be charged along with a new shipping cost.

**Arrival Inspection** Any transport damage must be noted on the delivery note before signing. Discrepancies from the packing slip must be reported to the supplier within 3 working days.

**Storage** Solid wood products are acclimatized for indoor environments (15–20°C, approx. 37% RH). Store the products indoors. Unfinished products must be stored under plastic and on a flat surface